

NEC MultiSync® LCD2070NX





Fully featured office monitors with outstanding display quality and ergonomic performance.

- Ergonomics and safety complying to the highest industry standards incl. ISO 13406-2
- ErgoDesign®: Height adjustable stand (110 mm) with 90° Pivot features
- Safety of investment with analog/digital interface and integrated USB hub
- Versatile and easy installation (VESA standard) with NaViSet and NaViKey
- Stable and excellent picture quality with NTAA (Non-Touch-Auto-Adjustment) and S-IPS TFT display

NEC MultiSync® LCD2070NX

Panel Technology S-IPS TFT Screen Size [inch/cm] 20.1 / 51.0 Pixel Pitch [mm] 0.255	
Screen Size [inch/cm] 20.1 / 51.0	
<u> </u>	
Viewing Angle [°] 176 horizontal / 176 vertical (typ. at contrast ratio 5:1)	
176 horizontal / 176 vertical (typ. at contrast ratio 10:1)	
Contrast Ratio (typ.) 700:1	
Brightness (typ.) [cd/m²] 250	
Response Time (typ.) [ms] 16 (7 white / black; 9 black / white)	
Colours [Mio.] 16.77	
Horizontal Frequency [kHz] 31.5 - 91.1	
Vertical Frequency [Hz] 56.0 - 85.0	
Optimum Resolution 1600 x 1200 at 60 Hz	
Supported Resolutions 1440 x 900; 1400 x 1050; 1280 x 1024; 1280 x 960; 1152 x 864; 1024 x	768; 832 x 624; 800 x
600; 720 x 400; 640 x 480	
Connectors Digital: 1 x DVI-D; Analog: 1 x mini D-sub 15 pin	
Plug & Play VESA DDC/Cl; DDC2B/2Bi; EDID Standard	
Adjust Functions Auto Adjust; Brightness; Colour Temperature Control; Contrast; Fine Adjust (a	
Management; Language Select; Monitor Information; NTAA (Non-Touch-Auto	o-Adjustment); On-
Screen-Display (OSD) lock-out; sRGB	
Safety and Ergonomics CE; TCO 03; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star; FCO	
C-UL or CSA; CCC; ISO 13406-2 (pixel failure class II); MPR II/ MPR III; RoHS	5
Power Consumption on Mode [W] 66 (typ.)	
Power Consumption Power-Saving Mode [W] < 3	
Power Supply 100-120 V/220-240 V; 0.75 A/0.4 A; internal power supply	
Ambient Temperature (operating) [°C] +5 to +35	
Ambient Humidity (operating) [%] 30 to 80	
VESA Mounting [mm] 100 x 100	
ErgoDesign®: Height adjustable Stand [mm] 110	
Screen Tilt / Swivel [°] -5 to +30 / -170 to +170	
Dimensions (W x H x D) [mm] 442 x 388.5 x 220	
Bezel Width [mm] 16.0	
Weight [kg] 8.6	
Cable Management yes	
Kensington Lock yes	
Benefits NaViSet®and NaViSet®Administrator compatible; Rapid Response Technology	y; sRGB Support; USB ver.
2.0 (4 down / 1 up)	
Audio Functions Option: MultiSync® Soundbar 70	
Colour Versions Silver Front Bezel, Black Back Cabinet	
Silver Front Bezel, Light Grey Back Cabinet	
Shipping Content Monitor; Power Cable; Signal Cable DVI-D - DVI-D; Signal Cable VGA - VGA;	USB Cable; CD-ROM;
Sales Office List; User Manual	
Warranty 3 years warranty incl. backlight	

























All hardware and software names are brand names and/or registered trademarks of the respective manufacturers. All rights reserved. All specifications are subject to change without notice. 03/li